



## FEATURES

- Label off intelligent function.
- Bad point detection.
- Paper out detection and easy paper loading.
- Fast printing, can finish one single label printing per second, save printing time greatly.
- Superior cooling performance, can deal with big workload printing.
- Re-printing function can effectively avoid losing label info or missing printing when lack of paper.
- After switch cover again, automatic positioning paper, which can effectively avoid printing dislocation, result in trouble and wasting label.

**SPECIFICATIONS**

<b>Code</b>	SX-TLP-410
<b>Printing method</b>	Direct thermal
<b>Resolution</b>	203dpi
<b>Printing speed</b>	127mm/s (5inch/s) - 150mm/s (optional)
<b>Max printing width</b>	104mm (4.09")
<b>Max printing length</b>	300mm (11.81") label
<b>Interface</b>	USB, USB+Serial+Ethernet, USB+Bluetooth, USB+Serial+Ethernet+Bluetooth, WiFi+USB, WUSE
<b>Print head</b>	150km (abrasive resistance)
<b>Commands</b>	TSC
<b>Max media roll</b>	OD 130mm (5.12")
<b>Min media roll</b>	ID 24mm (others available with external rear bracket), media paper type continuous paper, label paper, black mark paper
<b>Media width max</b>	120mm (4.72"), min 26.7mm (1.05")
<b>Media gap max</b>	100mm
<b>Label length</b>	20mm~300mm
<b>Accessories</b>	Power apdater, power cord, USB cable, CD, manual, external rear bracket (optional)
<b>Editing software</b>	Nicelabel SE
<b>Driver</b>	XP, Win7, Win8, Windows 10
<b>Character set</b>	GB18030 (simplified chinese)
<b>Print ASCII</b>	Font A 12x24ASCII, font b 9x24, chinese 24x24, 1D Code 39, 93, 128, ITF, ITF14, subsets A, B, C, codabar, EAN-8, EAN-13,EAN-14, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5)digits, add-on, MSI, MSIC, PLESSEY, CPOST 2D code QR code
<b>Graphics processing</b>	Support BMP/PCX/BAS
<b>Temperature</b>	Working 0-50°C, storage -20~70°C
<b>Humidity</b>	20%~85%, storage 5%~95%
<b>Power supply</b>	DC24V/2.5A
<b>RAM/Flash</b>	8MB/4M
<b>Power</b>	DC 24V, 2.5A
<b>Certificate</b>	CCC, CE, FCCID, ROHS
<b>Package size</b>	11x11x9"
<b>Package weight</b>	5.5lb
<b>Product size</b>	8.5x7x6.7"
<b>Product weight</b>	3lb

*\*The specifications and external design are subject to change without notice for further improvement.*